

BDPSW-1515

Fully-automatic Pallet Stretch Wrapper

MODEL SERIES:

turn



OPTIONS:

1. Turntable diameter 1650 mm, 1800 mm, or 2000 mm
2. Wrapping height 2000 mm or 2400 mm
3. Access ramp for loading
4. Ring bearing structure turntable for extra heavy loads. Top plate press for light products

BANDMAEQUIPCORPLIMITED

contact@bandmainfo.com | www.bandmainfo.com

Corporate Office: Ferdeplex, A-16, Swarn Park Extension, Mundka Colony, New Delhi-110041

Main Features:

1.	PLC controlled, easy wrapping program setting.
2.	Both one touch automatic programs & manual run are available.
3.	Turntable speed and carriage speed adjustable on panel.
4.	Turntable stop start & stop.
5.	Turntable home position.
6.	Automatic detection of pallet height by photocell.
7.	Open type carriage for easy film threading.
8.	Carriage driven by dual chain system

Technical Specification:

Wrap speed	30 - 40 pallets/hour
Turntable diameter	1650 mm
Turntable speed	3 - 15 rpm
Max. load weight	1500 kgs
Wrapping height	1800 mm
Turntable height	82 mm
Carriage type	300% ratio
Wrapping settings	Wrap cycles/bottom wraps/overwrap
Carriage speed	5 meters/min max
Turntable motor	0.75 kW
Carriage lifter motor	0.37 kW
Power	1 PH 220 V-AC, 50/60 Hz
Film type	Thickness:17-35microns; Width:450-500 mm; Paper Core 76 mm; Max. weight 18 kgs

BANDMAEQUIPCORPLIMITED

contact@bandmainfo.com | www.bandmainfo.com

Corporate Office: Ferdeplex, A-16, Swarn Park Extension, Mundka Colony, New Delhi-110041