

BDS-1650

Fully-automatic Pallet Stretch Wrapper



Main Features:

- PLC controlled, easy wrapping program setting
- Both one touch automatic programs and manual run are available
- Turntable speed and carriage speed adjustable on panel
- Turntable stops start and stop
- Turntable home position
- Automatic detection of pallet height by photocell
- Open type carriage for easy film threading
- Carriage driven by chain system

Options:

- | | |
|---|--|
| <ul style="list-style-type: none"> ➤ Turntable diameter 1500 mm, 1800 mm or 2000 mm ➤ Wrapping height 1800 mm (upto 2000 mm to 2400 mm) | <ul style="list-style-type: none"> ➤ Access ramp for loading ➤ Turntable could be M-shaped ➤ Ring bearing structure turntable for extra heavy loads |
|---|--|

BANDMAEQUIPCORPLIMITED

contact@bandmainfo.com | www.bandmainfo.com

Corporate Office: Ferdeplex, A-16, Swarn Park Extension, Mundka Colony, New Delhi-110041

Basic Information

| MODEL | BDS-1650 (GUSTO) |
|------------------------------|--|
| TURNTABLE DIAMETER | 1650 mm |
| TURNTABLE SPEED | 3 - 15 rpm |
| MAX. LOAD CAPACITY | 1500 kgs |
| WRAPPING HEIGHT | 1800 mm |
| TURNTABLE HEIGHT | 82 mm |
| STRETCH RATIO | Upto 300% ratio |
| WRAPPING SETTINGS | Wrap Cycles (Bottom to Top/Top to Bottom) Overwrap |
| TURNTABLE MOTOR | 0.75 KW |
| CARRIAGE LIFTER MOTOR | 0.37 KW |
| POWER | 1 PH 220 V AC, 50 / 60 Hz |
| FILM TYPE | ● Film Thickness : 17-35 microns |
| | ● Width : 450-500 mm |
| | ● Paper Core : 76 mm |
| | ● Max. Weight : 18 kgs |

BANDMA EQUIP CORP LIMITED

contact@bandmainfo.com | www.bandmainfo.com

Corporate Office: Ferdeplex, A-16, Swarn Park Extension, Mundka Colony, New Delhi-110041